SAN	ITORINI	Cleanaboo+	
7481-7490		WATER EASY TO CLEAN NON-FLAMMABLE ANTIBACTERI. REPELLENT	AL WEATHERPROOF
	Composition	100% olefin	
	Weight	230 g/m²± 5%	
	Width	140± 2 cm	
	Туре	woven fabric	
	Brand	outdoor fabric	
	Abrasion resistance PN-EN ISO 12947-2:2017-02	21 000 rubs	B Maintenance
	Fuzzing and pilling PN-EN ISO 12945-2:2002	4-5	A
~	Seam slippage PN-EN ISO 13936-2:2005	3,6 warp 3,0 weft	A A
	Wet rubbing PN-EN ISO 105-X12:2016-08	4-5	A ×
	Dry rubbing PN-EN ISO 105-X12:2016-08	4-5	A
·?	Colour fastness to light PN-EN ISO 105-X12:2016-08	7/8	A 🕅
2	Cigarette test PN-EN 1021-1:2014-12	PN-EN ISO 105-B02	×

- 1. The level of Cleanaboo and Cleanaboo+ protection can decrease after each cleaning of the fabric, but the process does not affect the look.
- 2. Respective fabric batches may differ slightly in shade from the colours presented in the sampler.
- Toptextil Sp. z o.o. is not liable for mechanical damage and such as may be attributable to the improper use and/or cleaning of the fabric.
- Bobbling and pilling are caused by the properties of the fabric and impossible to avoid entirely. This is a natural process, which occurs as the fabric is used.
- 5. Due to friction against the fabric, colourants can migrate from darker to brighter fabrics.
- 6. Long-term exposure to sunlight can cause discolouration.
- According to ISO 13936, the proper thickness of the bead is 33-35 of the stitching per 10 cm of the fabric with the minimum distance of the stitching from the edge of the fabric of at least 1.5 cm.
- 8. It is assumed that depending on the type of fabric, resistance to abrasion within the scope of 2,000-4,000 Martindale cycles corresponds with the period of 1 year of the proper use of the fabric.