

## **KONGO**

721-739, 761-775

Composition

Weight

Width

Туре

Brand



EASY TO CLEAN



PETPROOF





100% olefin

 $230 \text{ g/m}^2 \pm 5\%$ 

142 ± 3 cm

woven fabric

upholstery fabric

M <sub>s</sub>	Abrasion resistance PN-EN ISO 12947-2:2017-02	18 000 rubs	В
	Fuzzing and pilling PN-EN ISO 12945-2:2002	4-5	А
×	Seam slippage PN-EN ISO 13936-2:2005	4   warp 4   weft	А
	Antimicrobal activity EN ISO 2743:2013		✓

- The level of Cleanaboo and Cleanaboo+ protection can decrease after each cleaning of the fabric, but the process does not affect the look
- Respective fabric batches may differ slightly in shade from the colours presented
- Toptextil Sp. z o.o. is not liable for mechanical damage and such as may be attributable to the improper use and/or cleaning of the fabric
- Bobbling and pilling are caused by the properties of the fabric and impossible to avoid entirely. This is a natural process, which occurs as the fabric is used.
- Due to friction against the fabric, colourants can migrate from darker to brighter 5.
- Long-term exposure to sunlight can cause discolouration.
- According to ISO 13936, the proper thickness of the bead is 33-35 of the stitching per 10 cm of the fabric with the minimum distance of the stitching from the edge of the fabric of at least 1.5 cm.
- It is assumed that depending on the type of fabric, resistance to abrasion within the scope of 2,000-4,000 Martindale cycles corresponds with the period of 1 year of the proper use of the fabric.

Maintenance













