



MAGIC VELVET 3D

2201-2260



WATER REPELLENT



PETPROOF



NON-FLAMMABLE



Composition	100% PES
Weight	430 g/m ² ± 5%
Width	142 ± 2 cm
Type	knitted fabric
Brand	upholstery fabric

Icon	Test Name	Standard	Result	Grade	Maintenance
	Abrasion resistance	PN-EN ISO 12947-2:2017-02	60 000 rubs	A	
	Fuzzing and pilling	PN-EN ISO 12945-2:2002	5	A	
	Seam slippage	PN-EN ISO 13936-2:2005	3 warp 3 weft	A	
	Wet rubbing	PN-EN ISO 105-X12:2016-08	4	A	
	Dry rubbing	PN-EN ISO 105-X12:2016-08	4	B	
	Cigarette test	PN-EN 1021-1:2014-12		✓	

- The level of Cleanaboo and Cleanaboo+ protection can decrease after each cleaning of the fabric, but the process does not affect the look.
- Respective fabric batches may differ slightly in shade from the colours presented in the sampler.
- Toptextil Sp. z o.o. is not liable for mechanical damage and such as may be attributable to the improper use and/or cleaning of the fabric.
- Bobbling and pilling are caused by the properties of the fabric and impossible to avoid entirely. This is a natural process, which occurs as the fabric is used.
- Due to friction against the fabric, colourants can migrate from darker to brighter fabrics.
- Long-term exposure to sunlight can cause discolouration.
- According to ISO 13936, the proper thickness of the bead is 33-35 of the stitching per 10 cm of the fabric with the minimum distance of the stitching from the edge of the fabric of at least 1.5 cm.
- It is assumed that depending on the type of fabric, resistance to abrasion within the scope of 2,000-4,000 Martindale cycles corresponds with the period of 1 year of the proper use of the fabric.