


MAGIC VELVET

 2201-2260



WATER REPELLENT



PETPROOF



NON-FLAMMABLE



Composition	100% PES
Weight	300 g/m ² ± 5%
Width	142 ± 3 cm
Type	knitted fabric
Brand	upholstery fabric



Abrasion resistance
PN-EN ISO 12947-2:2017-02

60 000 rubs

A

Maintenance



Fuzzing and pilling
PN-EN ISO 12945-2:2002

5

A



Seam slippage
PN-EN ISO 13936-2:2005

3 | warp
3 | weft

A



Wet rubbing
PN-EN ISO 105-X12:2016-08

4

A



Dry rubbing
PN-EN ISO 105-X12:2016-08

4

B



Cigarette test
PN-EN 1021-1:2014-12

✓



- The level of Cleanaboo and Cleanaboo+ protection can decrease after each cleaning of the fabric, but the process does not affect the look.
- Respective fabric batches may differ slightly in shade from the colours presented in the sampler.
- Toptextil Sp. z o.o. is not liable for mechanical damage and such as may be attributable to the improper use and/or cleaning of the fabric.
- Bobbling and pilling are caused by the properties of the fabric and impossible to avoid entirely. This is a natural process, which occurs as the fabric is used.
- Due to friction against the fabric, colourants can migrate from darker to brighter fabrics.
- Long-term exposure to sunlight can cause discolouration.
- According to ISO 13936, the proper thickness of the bead is 33-35 of the stitching per 10 cm of the fabric with the minimum distance of the stitching from the edge of the fabric of at least 1.5 cm.
- It is assumed that depending on the type of fabric, resistance to abrasion within the scope of 2,000-4,000 Martindale cycles corresponds with the period of 1 year of the proper use of the fabric.